



• The sewing machine complies with the "Juki Group Green Procurement Guidelines" on the use of hazardous substances, which is stricter than other restrictions, such as those of the RoHS Directive.

For details of JUKI ECO PRODUCTS, refer to: https://www.juki.co.jp/en/company/e






4220 W 104 ST, SUITE 1A HIALEAH, FL 33018 PHONE: 305-594-0059 https://www.juki.com

\* Specifications and appearance are subject to change without prior notice for improvement.

\* Read the instruction manual before putting the machine into service to ensure safety.

\* This catalogue prints with environment-friendly soyink on recycle paper.

\* Paper from responsible sources FS™CC001712





### Preloaded & Custom Patterns

Elevate your production with the pre-loaded and custom patterns offered on the PLC-2760LC series. Featuring an array of meticulously curated pre-programmed patterns, the PLC-2760LC series offers unparalleled design versatility. What sets this machine apart is its innovative 1-needle and 2-needle setup, empowering you to effortlessly create bespoke patterns, tailored to your exact specifications.




#### **FEATURES**

## **Electronically Controlled Adjustments**

A dedicated control box allows for logical interface for the operator to select the applicable pattern.

The easy to navigate software makes selecting and changing stitching patterns simple for the operator.



## Vertical-Axis Double-Capacity Hook is Adopted

Utilizes a design which allows adjustment (screw) for the needle guard opening volume. As adjustment for the needle guard is simple, sections of the needle guard are hardened to prevent wearing of the blade point on the hook and skipped stitches.



## Digitally Control Stitch Length

The sewing machine is able to control the stitch length digitally.



## "One-Touch" Bobbin Winding Device

Bobbin winding system eliminates the requirement to manually wind the bobbin during the beginning of operation. Users can simply set the bobbin to enable auto winding.



#### Superior Basic Performance that Produces High Responsiveness to Materials

## Longer Distance from Machine Arm to Needle Working Area

Superior workability for larger sewing operation and extra heavy material.




## **Synchronizer Installed**

The synchronizer enables you to halt the needle at different pre-set positions, making it perfect for tasks like corner stitching or any process that necessitates precise up or down needle placement.



# Walking Foot Alternating Vertical Movement Mechanism that Prevents Irregular Stitches

The sewing machine incorporates a mechanism which maintains a steady balance of alternating vertical movement of the walking foot and presser foot even when the material is changed. Maximum alternating height is featured with 9mm, thereby allowing smooth passage when overcoming the step.



## **OPTIONAL GAUGES**

#### 2-Needle

	Part		Throat Plate	Feed Dog	Needle Clamp	Presser Foot	Walking Foot	Side Cover (Asm.)
	Shape							
Part No.	Needle Gauge	6mm	40131017	40130925	RDV820015-6	RDV820020-6	RDV820048-6	40134017
		8mm	40153188	40153187	RDV820015-8	RDV820020-8	RDV820048-8	40134018
		10mm	40130066	40130063	RDV820015-10	RDV820020-10	RDV820048-10	40134019