Bird's nest prevention device



This is a retrofittable optional kit to prevent the "bird's nest" at the start of sewing.

This device prevents the "bird's nest" that occurs on a bartacking sewing machine at the start of sewing. It automatically clamps the needle thread at the start of sewing and cuts excess thread with the built-in heat cutter to achieve the optimum needle thread amount. Beautiful stitches are realized by the quality improvement at the start of sewing and the effect of bird's nest prevention.



Needle thread clamping mechanism



It holds the needle thread after thread trimming and prevents the needle thread from getting caught on the back side of the fabric.

Needle thread trimming mechanism



Newly adopted heat cutter can cut from thin thread to thick thread.

Device part number by Model

Applicable models	Part Number		
LK1900B/BN	JSH-LK19PFU/J		

Operating voltage: Single-phase 200 to 240V

Using the remaining short thread throat plate kit together will make the stitches on the back of the fabric more beautiful.

Part Number 40193911/40194944

Bird's nest prevention



Bird's nest prevention Shorter-thread remaining



List of available patterns

Event from I K standard nottorna

Excerpt from LK standard patterns							
	No.	Stitch diagram	Sewing size(mm) Length- Cross-				
Large size bartacking	1 (51)	**************************************	1N 42	2.0	wise 16		
	2	######################################		2.0	10		
	3*	₩₩₩₩ 		2.5	16		
	4*	***************************************		3.0	24		
	5	*\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	28	2.0	10		
	6*			2.5	16		
	7	711111111111 1	36	2.0	10		
	8*	}		2.5	16		
	9*	<u> </u>	56	3.0	24		
	10*	***************************************	64	3.0	24		
Small size bartacking	11	% \\\	21	2.5	6		
	12	THE THE TAXABLE PROPERTY.	28	2.5	6		
	13		36	2.5	6		
Large size bartacking	37	7	90	3	24		
Knit goods bartacking	38		28	2	8		
Use the patterns with * marks for sewing denim							

Use the patterns with * marks for sewing denim.



CUSTOMER BUSINESS COMPANY

2-11-1, TSURUMAKI, TAMA-SHI, TOKYO 206-8551, JAPAN PHONE: (81) 42-357-2360 FAX: (81) 42-357-2380 https://www.juki.co.jp/en

- * Specifications and appearance are subject to change without prior notice for improvement.
- * Read the instruction manual before putting the machine into service to ensure safety.
- * This catalogue prints with environment-friendly soyink on recycle paper.
- * Paper from responsible sources FSC™ C001712